

Maze Nails

Product Specification Sheet

Hot-Dip Galvanized Plain Shank Asphalt & Fiberglass Shingle **Nails**

Stock Number: R105

MATERIAL LENGTH 2" **SHANK DIAMETER** 0.121" **HEAD DIAMETER** .375" **SHANK STYLE** Smooth **POINT STYLE** COATING

APPROX. NAILS PER LB

Medium Carbon Steel

40 degree diamond

Double Hot-Dip Galvanized

136.0

Product Description

Designed for the secure application of asphalt and fiberglass shingles on new construction and re-roofing jobs. STORMGUARD® Double Hot-Dipped Zinc-Coating provides extra corrosion-resistance in sea coastal areas. Manufactured to meet federal spec. ASTM F1667 and ASTM spec. A-153 for hot-dip zinc coating. Nails should be long enough to penetrate 3/4" into the wood deck lumber, or completely through plywood decking. All Maze Nails are 100% Made in the U.S.A. SIZES AND OUANTITIES COMMONLY USED On A New Roof - 1-1/4" -320 nails per sq. or 1-3/4 lbs. Over An Old Roof – 1-3/4" - 320 nails per sq. or 2-1/4 lbs.



Disclaimer: This image represents an entire series of nails, so the length may not be the exact match to the nail in this spec sheet

100% MADE IN THE USA

Generated on: 6/17/2020