

## Maze Nails

## **Product Specification Sheet**

## Hot-Dip Galvanized Plain Shank Asphalt & Fiberglass Shingle Nails

Stock Number: R104

**MATERIAL** 

**LENGTH** 

**SHANK DIAMETER** 

**HEAD DIAMETER** 

**SHANK STYLE** 

**POINT STYLE** 

COATING

APPROX. NAILS PER LB

Medium Carbon Steel

1-23/32" OAL

0.121"

.375"

Smooth

40 degree diamond

Double Hot-Dip Galvanized

145.0

## **Product Description**

Designed for the secure application of asphalt and fiberglass shingles on new construction and re-roofing jobs.

STORMGUARD® Double Hot-Dipped Zinc-Coating provides extra corrosion-resistance in sea coastal areas. Manufactured to meet federal spec. ASTM F1667 and ASTM spec.

A-153 for hot-dip zinc coating. Nails should be long enough to penetrate 3/4" into the wood deck lumber, or completely through plywood decking. All Maze Nails are 100% Made in the U.S.A. SIZES AND QUANTITIES COMMONLY USED On A New Roof – 1-1/4" - 320 nails per sq. or 1-3/4 lbs. Over An Old Roof – 1-3/4" - 320 nails per sq. or 2-1/4 lbs.



Disclaimer: This image represents an entire series of nails, so the length may not be the exact match to the nail in this spec sheet

\*100% MADE IN THE USA\*

Generated on: 6/17/2020

WWW.MAZENAILS.COM

PH-800.435.5949

**INFO@MAZENAILS.COM**